



RoHS 指令対応品

呼 び	呼 び		各 部 の 寸 法										標準色	適合電線範囲		適合工具	一箱入数			
	規格	ビニル	規格	ナイロン	d ₂	B	φd ₁	F ₁	l ₂	l	L ₁	板厚		燃線mm ²	AWG					
ス ト ー ト 型	UL	LF	AVH1.25-3	APH1.25-3	3.2	5.5	3.3	6.6	9.5	13.8	18.8	0.8	赤	∩	20-16	3号D 34号 DH-1B AC-5N-D	500 (100×5)			
	UL	LF	AVH1.25-4	APH1.25-4	4.3	8.0		7.3										9.5	15.8	20.8
	UL	LF	AVH1.25-5	APH1.25-5	5.3	11.5		10.0										20.2	25.2	
	UL	LF	AVH1.25-6	APH1.25-6	6.4	11.5	3.9	8.3	9.5	16.8	21.8	0.8	青	∩	16-14	4号D 34号 DH-1B AC-5N-D	500 (100×5)			
	UL	LF	AVH2-3	APH2-3	3.2	8.0														
	UL	LF	AVH2-4	APH2-4	4.3	8.5														
	UL	LF	AVH2-5	APH2-5	5.3	9.5														
	UL	LF	AVH2-6	APH2-6	6.4	12.0	4.9	8.3	14.0	17.8	26.5	1.0	黄	2.63-4.6	12	5号 DH-1B AC-5N-D	400 (100×4)			
	UL	LF	AVH2-8	APH2-8	8.4	8.4														
	UL	LF	AVH3.5-4	APH3.5-4	4.3	8.5	5.4	10.2	14.0	21.3	29.0	1.0	黄	∩	12-10	5号 DH-1B AC-5N-D	300 (100×3)			
	UL	LF	AVH5.5-4	APH5.5-4	4.3	9.5														
	UL	LF	AVH5.5-5	APH5.5-5	5.3	12.0														
	UL	LF	AVH5.5-6	APH5.5-6	6.4	12.0														
	UL	LF	AVH5.5-8	APH5.5-8	8.4	15.0	6.0	8.3	13.5	17.8	26.0	1.0	黄	2.63-4.6	12	5号 DH-1B AC-5N-D	200 (100×2)			
UL	LF	AVH5.5-8	APH5.5-8	8.4	15.0															

- 各呼びの印は、UL登録品、CSA登録品です。
- CSA登録品としてご使用の際は、注文時にご指示ください。カートンがCSA品用となります。
- ()は、BPH形の寸法です。