



RoHS 指令対応品

呼び	規格	呼び	規格	タイプ	各部の寸法							標準色	適合電線範囲		適合工具	一箱入数												
					B	φ d ₁ BV/ BP	F ₁	l ₂	l	L ₁	板厚		H	撚線mm ²			AWG											
ストリート形		AVAP-0.5	APAP-0.5	I	1.6	2.2	7.0	9.5	11.0	16.5	0.5	—	黄	0.3-0.5	22-20	DS05N, DH-1B	* 1,000											
		AVAP-1.25S	APAP-1.25S		1.0	3.3	9.7		14.0	19.2	0.8		—	赤	0.5 ~ 1.65	20-16	3号D 34号, 34S DH-1B AC-5N-D	500 (100×5)										
		AVAP-1.25M	APAP-1.25M		2.1		12.7		17.0	22.2																		
		AVAP-1.25	APAP-1.25		3.1		9.0		13.3	18.5																		
		AVAP-1.25-9	APAP-1.25-9		2.1	3.9	9.0		10.2	14.5									19.7	21.0	26.2	—	青	1.04 ~ 2.63	16-14	4号D 34号, 34S DH-1B AC-5N-D	300 (100×3)	
		AVAP-1.25-9B	APAP-1.25-9B		3.1																							16.7
		AVAP-1.25-10	APAP-1.25-10		2.1	4.1	9.0		10.2	14.5									19.2	21.0	25.7	—	—	—	—	—	—	—
		AVAP-1.25L	APAP-1.25L		3.1																							
		AVAP-2M	APAP-2M		3.1	4.7	9.0		13.3	18.0									21.0	25.7	—	—	—	—	—	—	—	—
		AVAP-2	APAP-2		2.1																							
		AVAP-2-9	APAP-2-9		3.1	6.4	—		14.4	20.7									28.4	32.2	—	—	—	—	—	—	—	—
		AVAP-2-9B	APAP-2-9B		3.1																							
		AVAP-2L	APAP-2L		2.1	4.5	9.0		13.3	18.0									21.0	25.7	—	—	—	—	—	—	—	—
		AVAP-2LB	APAP-2LB		3.2																							
	AVAP-5.5	APAP-5.5	3.3	6.4	—	14.4	20.7	27.9	31.7	—		—							—	—	—	—	—	—				
	AVAP-5.5L	APAP-5.5L	4.5								18.2		24.5	32.2														
	AVAP-5.5B	APAP-5.5B	4.5								13.0		19.3	27.0														
拡管形		BVAP-0.5	—	II	1.6	3.2	—	7.0	11.0	16.0	0.5	—	黄	0.3~0.5	22-20	DS05N, DH-1B	* 1,000											
		BVAP-1.25S	BPAP-1.25S		1.0	4.1	4.0	9.0	13.3	18.0	17.0		21.7	0.8	—	赤	0.5 ~ 1.65	20-16	3号D 34号, 34S DH-1B AC-5N-D	500 (100×5)								
		BVAP-1.25M	BPAP-1.25M		2.1																12.7	17.0	21.7					
		BVAP-1.25	BPAP-1.25		3.1																9.0	13.3	18.0					
		BVAP-1.25-9	BPAP-1.25-9		2.1	4.7	4.5	9.0	13.3	18.0	21.0		25.7								—	—	—	—	—	—		
		BVAP-1.25-9B	BPAP-1.25-9B		3.1																						16.7	17.0
		BVAP-1.25-10	BPAP-1.25-10		2.1	6.4	—	14.4	20.7	27.9	31.7		—								—	—	—	—	—	—	—	
		BVAP-1.25L	BPAP-1.25L		3.1																							16.7
		BVAP-2M	BPAP-2M		3.1	4.5	9.0	13.3	18.0	21.0	25.7		—								—	—	—	—	—	—	—	
		BVAP-2	BPAP-2		2.1																							12.7
		BVAP-2-9	BPAP-2-9		3.1	6.4	—	14.4	20.7	27.9	31.7		—								—	—	—	—	—	—	—	
		BVAP-2-9B	BPAP-2-9B		3.1																							16.7
		BVAP-2L	BPAP-2L		2.1	4.5	9.0	13.3	18.0	21.0	25.7		—								—	—	—	—	—	—	—	
		BVAP-2LB	BPAP-2LB		3.2																							16.7
	BVAP-5.5	—	3.3	6.4	—	14.4	20.7	27.9	31.7	—	—	—	—								—	—	—	—				
	BVAP-5.5L	—	4.5											18.2	24.5	31.7												
	BVAP-5.5B	—	4.5											13.0	19.3	26.5												
Iスト形		AVAP-1.25TU	APAP-1.25TU	II	3.0	3.3	13.2	9.5	21.5	26.7	0.8	1.8	赤	0.5~1.65	20-16	(注1)	500 (100×5)											
		AVAP-2TU	APAP-2TU		3.9	13.2												21.5	26.7									
拡管形		BVAP-1.25TU	BPAP-1.25TU	II	3.0	4.1	13.2	9.0	21.5	26.2	0.8	1.8	赤	0.5~1.65	20-16	(注1)	500 (100×5)											
		BVAP-2TU	BPAP-2TU		4.7	13.2												21.5	26.2									

1. 各呼びの印は、UL登録品、CSA登録品です。
2. CSA登録品としてご使用の際は、注文時にご指示ください。
カートンがCSA品用となります。
(注1) 3号D、34号、34S、DH-1B、AC-5N-D (注2) 4号D、34号、34S、DH-1B、AC-5N-D
3. *印は100個箱入り数量です。

板状形端子は通常の電流よりも60%~70%位の目安でご使用下さい。