







〈80°菱形 ポジ〉

品 番	内接円(φ)	厚さ(T)	逃げ角
CC_0602	6.35	2.38	7°
CC_09T3	9.525	3.97	7°

形 状	品 番	インチ系	コーナ R	PVDコーテッド 微粒子超硬								超硬 KM1	適合ホルダ 参照ページ	ブレーカ適用範囲
				ST4	ZM3	QM3	VM1	TM4	DT4	DM4	CP1	CP7		
 AM3	CCGT060200FNAM3		0.03											
	060202FNAM3		0.2											
	060204FNAM3		0.4											
	060201MFNAM3		*0.08											
	060202MFNAM3		*0.18											
	060204MFNAM3		*0.38											
	CCGT09T300FNAM3		0.03											
	09T302FNAM3		0.2											
	09T304FNAM3		0.4											
	09T301MFNAM3		*0.08											
	09T302MFNAM3		*0.18											
	09T304MFNAM3		*0.38											
 AZ7	CCMT060202FNAM3		0.2											
	060204FNAM3		0.4											
	CCMT09T302FNAM3		0.2											
	09T304FNAM3		0.4											
	09T308FNAM3		0.8											
 AZ8	CCGT060200AZ7		0.03											
	060201MAZ7		*0.08											
	060202MAZ7		*0.18											
	CCGT09T300AZ7		0.03											
	09T301MAZ7		*0.08											
	09T302MAZ7		*0.18											
 F1 右勝手を示す	09T304MAZ7		*0.38											
	CCMT060202ENAAZ8		0.2											
	060204ENBAZ8		0.4											
	060208ENBAZ8		0.8											
	CCMT09T302ENAAZ8		0.2											
	09T304ENBAZ8		0.4											
 KHG	09T308ENBAZ8		0.8											
	CCGT060201F ^R /F1		0.1	R		R		R						
	060202F ^R /F1		0.2	R		R		R						
	060204F ^R /F1		0.4	R		R		R						
	CCGT09T302F ^R /F1		0.2	R		R		R						
	09T304F ^R /F1		0.4	R		R		R						
	CCET0602005 ^R /KHG		0.05											
	0602008 ^R /KHG		0.08											
	0602018 ^R /KHG		0.18											
	060202 ^R /KHG		0.2											
	CCET09T3005 ^R /KHG		0.05											
	09T3008 ^R /KHG		0.08											
	09T3018 ^R /KHG		0.18											
	09T302 ^R /KHG		0.2											

*R記号(O1M, O2M, O4M)については被削部品のR指示がR0.1, R0.2, R0.4以下の加工にご使用できます。

● : 標準在庫 ● : 新標準在庫 ■ : 標準在庫廃止予定品 ★ : 標準在庫品(特定)