




| 共通仕様 | |
|------|-------------------------------|
| 精度等級 | JIS N8級 (JIS B 1702-1:1998) * |
| 歯形 | 並歯 |
| 圧力角 | 20° |
| 材料 | S45C |
| 熱処理 | — |
| 歯面硬度 | (194HB以下) |
| 表面処理 | 黒染 |

*モジュール0.8以下の製品は、表記精度等級「相当品」です。



S1

| カタログ記号 | モジュール | 歯数 | 形状 | 穴径 | ボス径 | 基準円直径 | 歯先円直径 | 歯幅 | ボス長さ | 全長 | キーみぞ 幅×深さ |
|------------|-------|-----|-----------|-----------------|------|-------|-------|----|------|----|--------------|
| | | | | A _{H7} | B | C | D | | | | |
| SSY0.8-20 | m0.8 | 20 | S1 | 5 | 13.5 | 16 | 17.6 | 4 | 8 | 12 | — |
| SSY0.8-25 | | 25 | S1 | 5 | 17 | 20 | 21.6 | | | | |
| SSY0.8-30 | | 30 | S1 | 5 | 20 | 24 | 25.6 | | | | |
| SSY0.8-40 | | 40 | S1 S1T | 5 | 25 | 32 | 33.6 | | | | |
| SSY0.8-40A | | | | 6 | | | | | | | |
| SSY0.8-50 | | 50 | S1 S1T | 5 | 25 | 40 | 41.6 | | | | |
| SSY0.8-50A | 6 | | | | | | | | | | |
| SSY1-12 | m1 | 12 | S1 | 5 | 9 | 12 | 14 | 6 | 8 | 14 | — |
| SSY1-12A | | | S1T | | | | | | | | |
| SSY1-14 | | 14 | S1 | 5 | 11 | 14 | 16 | | | | |
| SSY1-14A | | | S1T | | | | | | | | |
| SSY1-15 | | 15 | S1 | 6 | 12 | 15 | 17 | | | | |
| SSY1-15A | | | S1T | | | | | | | | |
| SSY1-16 | | 16 | S1 | 6 | 13 | 16 | 18 | | | | |
| SSY1-16A | | | S1T | | | | | | | | |
| SSY1-18 | | 18 | S1 | 6 | 14 | 18 | 20 | | | | |
| SSY1-18A | | | S1T | | | | | | | | |
| SSY1-20 | | 20 | S1 | 6 | 16 | 20 | 22 | | | | |
| SSY1-20A | | | S1T | 6 | | | | | | | |
| SSY1-20B | | | S1T | 8 | | | | | | | |
| SSY1-24 | | 24 | S1 | 6 | 16 | 24 | 26 | | | | |
| SSY1-24A | | | S1T | | | | | | | | |
| SSY1-25 | | 25 | S1 | 6 | 16 | 25 | 27 | | | | |
| SSY1-28 | | 28 | S1 | 6 | 16 | 28 | 30 | | | | |
| SSY1-28A | | | S1T | | | | | | | | |
| SSY1-30 | | 30 | S1 | 6 | 25 | 30 | 32 | | | | |
| SSY1-30A | | | S1T | 6 | | | | | | | |
| SSY1-30B | S1T | | 8 | | | | | | | | |
| SSY1-32 | 32 | S1 | 6 | 25 | 32 | 34 | | | | | |
| SSY1-35 | 35 | S1 | 6 | 25 | 35 | 37 | | | | | |
| SSY1-35A | | S1T | | | | | 8 | | | | |
| SSY1-36 | 36 | S1 | 6 | 25 | 36 | 38 | | | | | |
| SSY1-40 | 40 | S1 | 8 | 28 | 40 | 42 | | | | | |
| SSY1-40A | | S1T | | | | | | | | | |
| SSY1-45 | 45 | S1 | 8 | 28 | 45 | 47 | | | | | |
| SSY1-48 | 48 | S1 | 8 | 28 | 48 | 50 | | | | | |
| SSY1-48A | | S1T | | | | | | | | | |

