## シャフトカラー〈KSC-SP〉 🧸




## ●ご注文No.表記例 KSC1215SP

シャフトカラーNo.

\*スプロケットやタイミ ングプーリ等の位置決 め固定に最適クランプ 効果で確実に取付けら れます。





## ◇シャフトカラーサイズ表

シャフトカラーNo.	軸穴径 φD	総幅 B±0.1	外径 D1	ボルト穴 M	ボルト M×長さ	d	R	W	Х	Υ	質量(g)	¥
KSC 0308-SP	3	8	15	М 3	M 3× 8	3.4	3	1	4.5	3	10	850
KSC 0408-SP	4	8	15	М 3	M 3× 8	3.4	3	1	4.5	3	9	850
KSC 0508-SP	5	8	20	М 3	M 3×10	3.4	3	1	5.5	4	17	920
KSC 0510-SP	5	10	20	M 4	M 4×10	4.5	3.75	1	6	4	21	920
KSC 0608-SP	6	8	20	М 3	M 3×10	3.4	3	1	6	4	16	950
KSC 0610-SP	6	10	20	M 4	M 4×10	4.5	3.75	1	6	4	20	950
KSC 0808-SP	8	8	25	М 3	M 3×10	3.4	3	1.5	8	5	25	1,000
KSC 0810-SP	8	10	25	M 4	M 4×12	4.5	3.75	1.5	8	5	31	1,000
KSC 0812-SP	8	12	28	M 5	M 5×16	5.5	4.5	1.5	8	5	47	1,000
KSC 0815-SP	8	15	30	M 6	M 6×15	7	6	1.5	9	5	68	1,000
KSC 1010-SP	10	10	30	M 4	M 4×12	4.5	3.75	1.5	9	5	43	1,100
KSC 1012-SP	10	12	30	M 5	M 5×16	5.5	4.5	1.5	9	5	52	1,100
KSC 1015-SP	10	15	35	M 6	M 6×14	7	6	1.5	10	6	91	1,100
KSC 1210-SP	12	10	30	M 4	M 4×12	4.5	3.75	1.5	10	5	41	1,100
KSC 1212-SP	12	12	30	M 5	M 5×16	5.5	4.5	1.5	10	5	49	1,100
KSC 1215-SP	12	15	35	M 6	M 6×18	7	6	1.5	11	6	87	1,100
KSC 1310-SP	13	10	30	M 4	M 4×12	4.5	3.75	1.5	10	5	40	1,100
KSC 1315-SP	13	15	35	M 6	M 6×18	7	6	1.5	11	6	85	1,100
KSC 1510-SP	15	10	32	M 4	M 4×12	4.5	3.75	1.5	11	6	43	1,100
KSC 1512-SP	15	12	35	M 5	M 5×16	5.5	4.5	1.5	12	6	65	1,120
KSC 1515-SP	15	15	40	M 6	M 6×20	7	6	1.5	13	8	111	1,120
KSC 1610-SP	16	10	35	M 4	M 4×12	4.5	3.75	1.5	12	6	52	1,150
KSC 1612-SP	16	12	35	M 5	M 5×16	5.5	4.5	1.5	12	6	63	1,150