

旋削用チップ

「旋削用チップ」カタログの見方 B15 参照

三角形60°・ポジ・穴付き

型番	(mm)			型番	(mm)		
	IC	S	D1		IC	S	D1
TP_0802_	4.76	2.38	2.3	TPGT1102_	6.35	2.38	3.7
TP_0902_	5.56	2.38	2.8	TP_1103_	6.35	3.18	3.3
TPGB0902_	5.56	2.38	3.2	TP_1603_	9.525	3.18	4.7

形状	型番	寸法 (mm)		コーティング												DLC		超硬		ブレیکا適用範囲			
		サマーセット	CVD	CVDコーティング												PVDコーティング		超硬					
		RE	TN610 TN620 TN60	CCX	PVDサマーセット	CVDコーティング												PVDコーティング			超硬		
スーパーファイン	TPET 080201FL-USF	0.1																			B85 1		
	080202FR-USF	0.2																					
	080202FL-USF	0.2																					
	TPET 1103003FL-USF	0.03																					
	110301FR-USF	0.1																					
	110301FL-USF	0.1																					
	110302FR-USF	0.2																					
	110302FL-USF	0.2																					
	TPET 080202MFR-USF	<0.2																					
	080202MFL-USF	<0.2																					
	TPET 110301MFL-USF	<0.1																					
	110302MFR-USF	<0.2																					
110302MFL-USF	<0.2																						
アルミ非鉄	TPGT 090202AP	0.2																					
	090204AP	0.4																					
	090208AP	0.8																					
	TPGT 110302AP	0.2																					
	110304AP	0.4																					
	110308AP	0.8																					
鉄	TPGB 080202	0.2																					
	080204	0.4																					
	080208	0.8																					
	TPGB 090202	0.2																					
	090204	0.4																					
	TPGB 1102005	0.05																					
	110201	0.1																					
	110202	0.2																					
	110204	0.4																					
	TPGB 1103005	0.05																					
	110301	0.1																					
	110302	0.2																					
110304	0.4																						
110308	0.8																						
TPGB 160304	0.4																						
160308	0.8																						

・ コーナR(RE)寸法が不等号(例 : <0.05, <0.1, <0.2 など)で表示されていますチップは、コーナR(RE)がマイナス公差の製品を示します。

チップの販売個数は、1ケース10個入りです

● : 標準在庫

B 旋削チップ

- ブレیکا
特長
- ポジ
- C
- D
- R
- S
- T
- V
- W
- セラミック