

MSRS90




Fig. 1




Fig. 2




Fig. 3




Fig. 4

すくい角	
A.R.	R.R.
+7°	-10°




Fig. 5




Fig. 6




Fig. 7




Fig. 8

●ホルダ寸法

型 番		在庫	刃数	刃列	段数	寸 法 (mm)																形状	重量 (kg)
						DC	DCSFMS	DCB	DCCB ₁	DCCB ₂	LF	CBDP	KDP	KWW	APMX	DCCB ₃	DCCB ₄	DCCB ₅	DCCB ₆	CBDP ₂			
インロー部 インチ仕様	MSRS 90080R-1-4T	●	4	4	1	80	70	31.75	27	18	60	32	8	12.7	16.5	-	-	-	-	-	Fig. 1	1.4	
	90080R-2-4T	●	8		2						31				Fig. 2						1.2		
	90080R-4-4T	●	16		4						85				60						Fig. 3	1.5	
	90100R-1-6T	●	6	6	1	100	85	38.1	39	21	70	10	15.9	16.5	-	-	-	-	-	Fig. 1	2.3		
	90100R-2-6T	●	12		2						31			Fig. 2						2.1			
	90100R-4-6T	受	24		4						90			60						Fig. 3	3.2		
	90125R-1-8T	●	8	8	1	125	55	-	-	-	16.5	-	-	-	-	-	-	Fig. 4	2.6				
	90125R-2-8T	受	16		2						31							Fig. 5	2.4				
	90160R-1-8T	●	8	8	1	160	100	50.8	70	-	-	16.5	11	19.1	16.5	-	-	-	-	Fig. 4	4.3		
	90160R-2-8T	受	16		2							31			Fig. 5					4.1			
	90200R-1-10T	●	10	10	1	200	130	47.625	-	101.6	60	-	14	25.4	16.5	18	26	-	-	32	Fig. 6	6.7	
	90200R-2-10T	受	20		2										31						Fig. 7	6.6	
	90250R-1-12T	●	12	12	1	250	-	-	-	-	-	-	14	25.4	16.5	-	-	-	-	-	Fig. 6	12.6	
	90250R-2-12T	受	24		2										31						Fig. 7	12.5	
	90315R-1-14T	●	14	14	1	315	220	-	-	-	-	-	-	-	16.5	17	27	22	32	25	Fig. 8	16.1	
	90315R-2-14T	受	28		2										31						-	16.0	
ミリ仕様	MSRS 90080R-1-4T-M	●	4	4	1	80	70	27	20	13	60	24	7	12.4	16.5	-	-	-	-	-	Fig. 1	1.3	
	90080R-2-4T-M	●	8		2						31				Fig. 2						1.1		
	90080R-4-4T-M	●	16		4						85				60						Fig. 3	1.4	
	90100R-1-6T-M	●	6	6	1	100	85	32	45	-	70	30	8	14.4	16.5	-	-	-	-	-	Fig. 1	2.2	
	90100R-2-6T-M	●	12		2						31				Fig. 2						2.0		
	90100R-4-6T-M	受	24		4						90				60						Fig. 3	3.1	
	90125R-1-8T-M	●	8	8	1	125	40	55	-	-	-	33	9	16.4	16.5	-	-	-	-	28	Fig. 4	2.6	
	90125R-2-8T-M	受	16		2										31						Fig. 5	2.4	
	90160R-1-8T-M	●	8	8	1	160	110	-	-	-	66.7	-	-	-	16.5	14	20	-	-	-	Fig. 6	4.2	
	90160R-2-8T-M	受	16		2										31						Fig. 7	4.0	
	90200R-1-10T-M	●	10	10	1	200	140	60	-	101.6	60	-	40	14	25.7	16.5	18	26	-	-	32	Fig. 6	6.7
	90200R-2-10T-M	受	20		2											31						Fig. 7	6.6
	90250R-1-12T-M	●	12	12	1	250	-	-	-	-	-	-	40	14	25.7	16.5	-	-	-	-	-	Fig. 6	12.6
	90250R-2-12T-M	受	24		2											31						Fig. 7	12.5
	90315R-1-14T-M	●	14	14	1	315	220	-	-	-	-	-	-	-	16.5	17	27	22	32	25	Fig. 8	16.1	
	90315R-2-14T-M	受	28		2										31						-	16.0	

●：標準在庫
受：受注生産