

● チップ寸法 (VNB / VNB-NB / VNBTR)

型番	最小加工径	寸法 (mm)								材種						
		DMIN	H	LF	LU	WF	WF ₂	RE	LBB	θ	MEGA COAT	PVD	超硬	ダイヤモンド		
											PR1225	PR930	KW10	KPD001	KPD010	
VNBTR	0206-003	2	3.9	26.5	6	1.8	0.25	0.03	1.2	24°	●	●	●			
	0311-003	3		30.8	11	2.6	0.4		1.8		●	●	●			
	0411-003	4		39.8	20	3.5	0.5		2.7		23°	●	●	●		
	0420-003											●	●	●		
	0511-003	5		30.8	11	4.5	0.7		3.0		24°	●	●	●		
	0520-003	6		39.8	20	5.3	1.0					●	●	●		
	0620-003	7		49.8	30	6.2	1.0		0.1		24°	●	●	●		
	0630-003											●	●	●		
	0720-003											●	●	●		
	0730-003	7		49.8	30	6.2	1.0		●		●	●				
VNBTR	0206-01	2	3.9	26.5	6	1.8	0.25	0.1	1.2	24°	●	●	●			
	0311-01	3		30.8	11	2.6	0.4		1.8		●	●	●			
	0411-01	4		39.8	20	3.5	0.5		2.7		23°	●	●	●		
	0420-01											●	●	●		
	0511-01	5		30.8	11	4.5	0.7		3.0		24°	●	●	●		
	0520-01	6		39.8	20	5.3	1.0					●	●	●		
	0620-01	7		49.8	30	6.2	1.0		0.2		24°	●	●	●		
	0630-01											●	●	●		
	0720-01											●	●	●		
	0730-01	7		49.8	30	6.2	1.0		●		●	●				
VNBTR	0206-02	2	3.9	26.5	6	1.8	0.25	0.2	1.2	24°	●	●	●			
	0311-02	3		30.8	11	2.6	0.4		1.8		●	●	●			
	0411-02	4		39.8	20	3.5	0.5		2.7		23°	●	●	●		
	0420-02											●	●	●		
	0511-02	5		30.8	11	4.5	0.7		3.0		24°	●	●	●		
	0520-02	6		39.8	20	5.3	1.0					●	●	●		
	0620-02	7		49.8	30	6.2	1.0		0.3		15°	●	●	●		
	0630-02											●	●	●		
	0720-02											●	●	●		
	0730-02	7		49.8	30	6.2	1.0		●		●	●				
VNBTR	0206-003NB	2	3.9	26.5	6	1.8	0.25	0.03	-	15°	●	●	●			
	0311-003NB	3		30.8	11	2.6	0.4		●		●	●				
	0411-003NB	4		39.8	20	3.5	0.5		2.7		23°	●	●	●		
	0420-003NB											●	●	●		
	0511-003NB	5		30.8	11	4.5	0.7		3.0		24°	●	●	●		
	0520-003NB	6		39.8	20	5.3	1.0					●	●	●		
	0620-003NB	7		49.8	30	6.2	1.0		0.2		15°	●	●	●		
	0630-003NB											●	●	●		
	0720-003NB											●	●	●		
	0730-003NB	7		49.8	30	6.2	1.0		●		●	●				
VNBTR	0206-02NB	2	3.9	26.5	6	1.8	0.25	0.2	-	15°	●	●	●			
	0311-02NB	3		30.8	11	2.6	0.4		●		●	●				
	0411-02NB	4		39.8	20	3.5	0.5		2.7		23°	●	●	●		
	0420-02NB											●	●	●		
	0511-02NB	5		30.8	11	4.5	0.7		3.0		24°	●	●	●		
	0520-02NB	6		39.8	20	5.3	1.0					●	●	●		
	0620-02NB	7		49.8	30	6.2	1.0		0.3		15°	●	●	●		
	0630-02NB											●	●	●		
	0720-02NB											●	●	●		
	0730-02NB	7		49.8	30	6.2	1.0		●		●	●				
VNBTR	0411-003	4	3.9	30.8	11	3.6	1.0	0.03	-	-	●	●	●			
	0420-003			39.8	20				●		●	●				
	0511-003	5		30.8	11	4.6	1.3		●		●	●				
	0520-003			39.8	20				●		●	●				
VNBTR	0411-01	4	3.9	30.8	11	3.6	1.0	0.1	-	-	●	●	●			
	0420-01			39.8	20				●		●	●				
	0511-01	5		30.8	11	4.6	1.3		●		●	●				
	0520-01			39.8	20				●		●	●				

推奨切削条件 ● F36

● : 標準在庫
□ : 次期カタログより抹消予定

システムバーの販売個数は、1ケース5個入りです

チップ材種
旋削チップ
CERAMIC
外徑
スモールツール
内徑
溝入れ
突切り
ねじ切り
ドリル
ソリッドツール
ミリング
ターニング
イジヤマシン
部品
技術資料
SICK
索引

A
B
C
D
E
F
G
H
J
K
L
M
N
O
P
R
S
T