

T10寸法一覧表

<T10-15-A> 選択可能な材質：鋼材

歯数	寸法(mm)						適応軸穴径 (mm) ※軸穴公差H7																			
	PD	OD	LA	W	H	F	M	8	9	10	11	12	14	15	16	17	18	19	20	22	24	25	28	30	32	
12	38.20	36.35						43	28																	
14	44.56	42.70						47	34			10	11	12	14	15	16	17	18							
15	47.75	45.90						51	36			10	11	12	14	15	16	17	18	19	20					
16	50.93	49.05						57	41			10	11	12	14	15	16	17	18	19	20	22				
18	57.30	55.45						61	41				12	14	15	16	17	18	19	20	22	24	25			
20	63.66	61.80						69	50				12	14	15	16	17	18	19	20	22	24	25	28		
22	70.03	68.15						74	53				12	14	15	16	17	18	19	20	22	24	25	28		
24	76.39	74.55	22	17	2.5			83	63				12	14	15	16	17	18	19	20	22	24	25	28		
25	79.58	77.70						86	66				12	14	15	16	17	18	19	20	22	24	25	28		
26	82.76	80.90						86	66				12	14	15	16	17	18	19	20	22	24	25	28	30	
28	89.13	87.25						93	75				12	14	15	16	17	18	19	20	22	24	25	28	30	
30	95.49	93.65						99	78				12	14	15	16	17	18	19	20	22	24	25	28	30	
32	101.86	100.00						105	84				14	15	16	17	18	19	20	22	24	25	28	30	32	
36	114.59	112.75						118	90				14	15	16	17	18	19	20	22	24	25	28	30	32	
40	127.32	125.45						131	101				14	15	16	17	18	19	20	22	24	25	28	30	32	

<T10-15-B> 選択可能な材質：鋼材

歯数	寸法(mm)								適応軸穴径 (mm) ※軸穴公差H7																			
	PD	OD	LA	LB	W	H	K	D	F	M	8	9	10	11	12	14	15	16	17	18	19	20	22	24	25	28	30	
12	38.20	36.35						25	43	28																		
14	44.56	42.70						30	47	34				10	11	12	14	15										
15	47.75	45.90						33	51	36				10	11	12	14	15	16	17								
16	50.93	49.05						35	57	41				10	11	12	14	15	16	17								
18	57.30	55.45						37	61	41						12	14	15	16	17	18	19						
20	63.66	61.80						40	69	50						12	14	15	16	17	18	19	20	22				
22	70.03	68.15						40	74	53						12	14	15	16	17	18	19	20	22				
24	76.39	74.55	22		17	2.5		40	83	63						12	14	15	16	17	18	19	20	22				
25	79.58	77.70						40	86	66						12	14	15	16	17	18	19	20	22				
26	82.76	80.90						45	86	66						12	14	15	16	17	18	19	20	22	24	25		
28	89.13	87.25						45	93	75						12	14	15	16	17	18	19	20	22	24	25		
30	95.49	93.65						45	99	78						12	14	15	16	17	18	19	20	22	24	25		
32	101.86	100.00						50	105	84						14	15	16	17	18	19	20	22	24	25	28	30	
36	114.59	112.75					35	50	118	90						14	15	16	17	18	19	20	22	24	25	28	30	
40	127.32	125.45						50	131	101						14	15	16	17	18	19	20	22	24	25	28	30	

<T10-25-A> 選択可能な材質：鋼材

歯数	寸法(mm)						適応軸穴径 (mm) ※軸穴公差H7																				
	PD	OD	LA	W	H	F	M	8	9	10	11	12	14	15	16	17	18	19	20	22	24	25	28	30	32		
14	44.56	42.70						47	34	10	11	12	14	15	16	17	18										
15	47.75	45.90						51	36	10	11	12	14	15	16	17	18	19	20								
16	50.93	49.05						57	41	10	11	12	14	15	16	17	18	19	20	22							
18	57.30	55.45						61	41				12	14	15	16	17	18	19	20	22	24	25				
20	63.66	61.80						69	50				12	14	15	16	17	18	19	20	22	24	25	28			
22	70.03	68.15						74	53				12	14	15	16	17	18	19	20	22	24	25	28			
24	76.39	74.55	32	27	2.5			83	63				12	14	15	16	17	18	19	20	22	24	25	28			
25	79.58	77.70						86	66				12	14	15	16	17	18	19	20	22	24	25	28			
26	82.76	80.90						86	66				12	14	15	16	17	18	19	20	22	24	25	28	30		
28	89.13	87.25						93	75				12	14	15	16	17	18	19	20	22	24	25	28	30		
30	95.49	93.65						99	78				12	14	15	16	17	18	19	20	22	24	25	28	30		
32	101.86	100.00						105	84				14	15	16	17	18	19	20	22	24	25	28	30	32		
36	114.59	112.75						118	90				14	15	16	17	18	19	20	22	24	25	28	30	32		
40	127.32	125.45						131	101				14	15	16	17	18	19	20	22	24	25	28	30	32		

<T10-25-B> 選択可能な材質：鋼材

歯数	寸法(mm)								適応軸穴径 (mm) ※軸穴公差H7																			
	PD	OD	LA	LB	W	H	K	D	F	M	8	9	10	11	12	14	15	16	17	18	19	20	22	24	25	28	30	
14	44.56	42.70						30	47	34	10	11	12	14	15													
15	47.75	45.90						33	51	36	10	11	12	14	15	16	17											
16	50.93	49.05						35	57	41	10	11	12	14	15	16	17											
18	57.30	55.45						37	61	41				12	14	15	16	17	18									
20	63.66	61.80						40	69	50				12	14	15	16	17	18	19	20							
22	70.03	68.15						40	74	53				12	14	15	16	17	18	19	20							
24	76.39	74.55	32	45	27	2.5	13	40	83	63				12	14	15	16	17	18	19	20							
25	79.58	77.70						40	86	66				12	14	15	16	17	18	19	20							
26	82.76	80.90						45	86	66				12	14	15	16	17	18	19	20	22	24	25				
28	89.13	87.25						45	93	75				12	14	15	16	17	18	19	20	22	24	25				
30	95.49	93.65						45	99	78				12	14	15	16	17	18	19	20	22	24	25				
32	101.86	100.00						50	105	84				14	15	16	17	18	19	20	22	24	25	28	30			
36	114.59	112.75						50	118	90				14	15	16	17	18	19	20	22	24	25	28	30			
40	127.32	125.45						50	131	101				14	15	16	17	18	19	20	22	24	25	28	30			

※青塗部はタップ長さが不足する為、標準のセットスクリーンが付属されます。(P3 参照)

●製品コード例

S3 - **T10** - **25** - **24** **A** **F** - **19** **T2** **K**

S1：鋼材＋表面処理無し
S2：鋼材＋黒染
S3：鋼材＋無電解ニッケルメッキ

ブリー歯形

ブリー呼び幅
(使用ベルト幅mm)

ブリー歯数

ブリー形状

フランジ
P.3 表2参照

軸穴径(mm)

タップ加工
P.3 表3参照

キー溝(JS9公差)
P.3 表3参照