

被削材	P	鋼	F7030	MC5020	MP6120	MP6130	MP7130	MP7140	MP9120	MP9130	VP15TF	VP30RT	NX4545	サーマット	超硬	HTT10	寸法 (mm)			形状
	M	ステンレス鋼															IC	S	RE	
被削材	K	鋳鉄	E	●	●	●	●	●	●	●	●	●	●	●	●	●	13.4	3.97	1.5	形状
	N	非鉄金属																		
被削材	S	耐熱合金、チタン合金	G	●	●	●	●	●	●	●	●	●	●	●	●	●	13.4	3.97	-	形状
	H	高硬度鋼																		
被削材	S	耐熱合金、チタン合金	M	S	●	●	●	●	●	●	●	●	●	●	●	●	13.4	3.97	1.5	形状
被削材	S	耐熱合金、チタン合金	M	S	●	●	●	●	●	●	●	●	●	●	●	●	13.4	3.97	1.5	形状
被削材	S	耐熱合金、チタン合金	M	S	●	●	●	●	●	●	●	●	●	●	●	●	13.4	3.97	1.5	形状
被削材	S	耐熱合金、チタン合金	M	S	●	●	●	●	●	●	●	●	●	●	●	●	13.4	3.97	1.5	形状
被削材	S	耐熱合金、チタン合金	K	T	●	●	●	●	●	●	●	●	●	●	●	●	12.7	3.18	-	形状
被削材	S	耐熱合金、チタン合金	A	F	●	●	●	●	●	●	●	●	●	●	●	●	12.7	3.175	-	形状
被削材	S	耐熱合金、チタン合金	A	F	●	●	●	●	●	●	●	●	●	●	●	●	12.7	3.175	-	形状
被削材	S	耐熱合金、チタン合金	C	F	●	●	●	●	●	●	●	●	●	●	●	●	12.7	3.175	-	形状
被削材	S	耐熱合金、チタン合金	C	F	□	●	●	●	●	●	●	●	●	●	●	●	12.7	3.175	-	形状
ASX445	SEET13T3AGEN-JL	E	E	●	●	●	●	●	●	●	●	●	●	●	●	●	13.4	3.97	1.5	
ASX445	SEGT13T3AGFN-JP	G	F												●		13.4	3.97	-	
ASX445	SEMT13T3AGSN-FT	M	S	●													13.4	3.97	1.5	
ASX445	SEMT13T3AGSN-JH	M	S	●	●	●	●	●	●	●	●	●	●	●	●	●	13.4	3.97	1.5	
ASX445	SEMT13T3AGSN-JM	M	S	●	●	●	●	●	●	●	●	●	●	●	●	●	13.4	3.97	1.5	
コーナ角45°	SEKN1203AGTN	K	T											▲			12.7	3.18	-	
BF407 QBF407	SFAN1203ZFFR2	A	F												●		12.7	3.175	-	
	SFAN1203ZFFL2	A	F												●		12.7	3.175	-	
	SFCN1203ZFFR2	C	F												●		12.7	3.175	-	
	SFCN1203ZFFL2	C	F												□		12.7	3.175	-	