











被削材	P	鋼	コーティング		サーメット	超硬	寸法 (mm)					形状				
	M	ステンレス鋼	F7030	VP15TF	LC15TF	UP20M	NX2525	UTi20T	HTi10	TF15	L		IC	S	BS	RE
	TPMN160304	M	E*1	●	●	●	●	●	●	●	—	9.525	3.18	—	0.4	
	TPMN160308	M	E*2	●	●	●	●	●	●	●	—	9.525	3.18	—	0.8	
	TPMN160312	M	E*1		●				●		—	9.525	3.18	—	1.2	
	TPMN220404	M	E						●		—	12.7	4.76	—	0.4	
	TPMN220408	M	E*1	●	●	●			●	●	—	12.7	4.76	—	0.8	
	TPMN220412	M	E*1	●	●				●	●	—	12.7	4.76	—	1.2	
	TPNX1605N	N	E						●		—	9.525	5	—	—	
	XDGT1550PDER-G04	G	E	●						●	22	—	5	1.5	0.4	
	XDGT1550PDER-G08	G	E	●						●	22	—	5	1.1	0.8	
	XDGT1550PDER-G12	G	E	●						●	22	—	5	0.7	1.2	
	XDGT1550PDER-G16	G	E	●						●	22	—	5	0.4	1.6	
	XDGT1550PDER-G20	G	E	●						●	21.7	—	5	0.2	2.0	
	XDGT1550PDER-G30	G	E	●						●	20	—	5	0.6	3.0	
	XDGT1550PDER-G32	G	E	●						●	20	—	5	0.4	3.2	
	XDGT1550PDER-G40	G	E	●						●	19	—	5	0.5	4.0	
	XDGT1550PDFR-G04	G	F		●					●	22	—	5	1.5	0.4	
	XDGT1550PDFR-G08	G	F		●					●	22	—	5	1.1	0.8	
	XDGT1550PDFR-G12	G	F		●					●	22	—	5	0.7	1.2	
	XDGT1550PDFR-G16	G	F		●					●	22	—	5	0.4	1.6	
	XDGT1550PDFR-G20	G	F		●					●	21.7	—	5	0.2	2.0	
	XDGT1550PDFR-G30	G	F		●					●	20	—	5	0.6	3.0	
	XDGT1550PDFR-G32	G	F		●					●	20	—	5	0.4	3.2	
	XDGT1550PDFR-G40	G	F		●					●	19	—	5	0.5	4.0	
	XDGT1550PDFR-GL04	G	F							●	22	—	5	1.5	0.4	
	XDGT1550PDFR-GL08	G	F							●	22	—	5	1.1	0.8	

*1 HTi10のホーニングは"F"です。
 *2 HTi10のホーニングは"F"、NX2525のホーニングは"T"です。