













# ASX400

## インサート

用途	インサート 外観	呼び記号	精度	ホーニング	コーティング										サ-メット	超硬	寸法(mm)				形状			
					F7030	MC5020	MP6120	MP6130	MP7130	MP7140	MP9120	MP9130	VP15TF	VP30RT			NX4545	HT10	IC	S		BS	RE	
仕上げ-軽切削用	JLブレード 	SOET12T308PEER-JL	E	E	●	●	●	●	●	●	●	●	●	●	●	●	●			12.7	3.97	1.4	0.8	
軽-荒切削用	JMブレード 	SOMT12T308PEER-JM	M	E	●	●	●	●	●	●	●	●	●	●	●	●	●			12.7	3.97	1.4	0.8	
中-重切削用	JHブレード 	SOMT12T308PEER-JH	M	E	●	●	●	●	●	●	●	●	●	●	●	●	●			12.7	3.97	1.4	0.8	
重断続切削用	FTブレード 	SOMT12T320PEER-FT	M	E	●	●				●	●	●	●	●	●	●	●			12.7	3.97	0.5	2.0	
アルミウム合金切削用	JPブレード 	SOGT12T308PEFR-JP	G	F													●		12.7	3.97	1.4	0.8		



## ワイパーインサート

インサート外観	呼び記号	精度	ホーニング	サ-メット		寸法(mm)					形状
				NX2525	HT105T	L	W1	S	BS	RE	
	WOEW12T308PEER8C	E	E		●	12.5	13.2	3.97	8	0.8	
	WOEW12T308PETR8C	E	T	●		12.5	13.2	3.97	8	0.8	

● : 標準在庫品(インサートは、1ケース 10 個入りです)