

SANITARY CONVERSION FITTINGS

サニタリー変換継手



● CADデータフォルダ名: 52_Sanitary_Vacuum_Tanks

52 サニタリー管
真空配管部・タンク

■ オネジタイプ

Type	材質
SNZFA	SUS304

RoHS10

型式		呼び	R(PT)	L	A	B	d	d1	D1	¥基準単価	¥スライド単価
Type	No.									1~9コ	10~20
SNZFA	1S	3-40	3/8	40	50.5	43.5	23	11.0	17.3	4,500	4,050
		4	1/2	60						4,300	3,900
		4-40		40						4,300	3,890
		6	3/4	60						3,900	3,510
		6-40		40						3,800	3,420
	1.5S	8	1	60						3,800	3,420
		6-40	3/4	40						3,900	3,510
		8	1	40						3,800	3,420
		8-40		60						3,900	3,510
		10	1 1/4	65						4,200	3,830
2S	12	1 1/2	65	4,360	3,920						
	10	1 1/4	70	4,900	4,400						
	12	1 1/2	70	5,270	4,740						
	16	2	70	64.0	56.5	47.8	51	60.5	5,410	4,870	

Ⓢ表示数量超えはWOSIにてご確認ください。

■ ホースタイプ

Type	材質
SNHAD	SUS304
SNHADS	SUS316L

RoHS10

型式		呼び	ホース呼び内径	A	B	L	D	SNHAD		SNHADS	
Type	No.							¥基準単価	¥スライド単価	¥基準単価	¥スライド単価
								1~9コ	10~20	1~9コ	10~20
SNHAD	1S	1S	50.5	43.5	80	25.4	2,610	2,480	5,410	4,610	
		19	50.5	43.5	50	20.5	9,000	8,800	—	—	
	1.5S	1.5S	50.5	43.5	100	38.1	3,030	2,880	5,740	4,650	
		1.5S-1S	1S	50.5	43.5	100	25.4	7,800	7,300	—	—
	2S	2S	64.0	56.5	100	50.8	3,610	3,430	7,320	5,940	
		2S-1.5S	1.5S	64.0	56.5	100	38.1	9,360	8,800	—	—
	2.5S	2.5S	77.5	70.5	100	63.5	4,710	4,470	13,580	10,460	
		2.5S-2S	2S	77.5	70.5	100	50.8	12,720	—	—	—
	3S	3S	91.0	83.5	100	76.3	6,290	5,980	18,920	14,580	

ⓈNo.2.5S-2Sのみ10コ以上お見積り。

Ⓢ表示数量超えはWOSIにてご確認ください。

■ メネジタイプ

Type	材質
SNZFS	SUS304

RoHS10

型式		呼び	Rp	A	B	D	L	C	¥基準単価		¥スライド単価				
Type	No.								1~9コ	10~20	1~9コ	10~20			
SNZFS	1.5S	2	1/4	50.5	43.5	38.1	21	0.9	3,100	2,580					
		3	3/8						1.2	2,990	2,610				
		4	1/2						1.2	3,020	2,580				
	2S	3	3/8						1.2	4,070	3,380				
		4	1/2						64.0	56.5	50.8	21	1.2	3,950	3,380
		6	3/4						1.2	3,950	3,380				
	2.5S	4	1/2						1.2	5,080	4,350				
		6	3/4						77.5	70.5	63.5	21	1.2	5,220	4,350
		8	1						1.5	4,830	4,350				
		6	3/4						1.2	7,640	6,540				
3S	8	1	91.0	83.5	76.3	21	1.5	7,270	6,540						
	6	3/4	1.5	7,270	6,540										
	10	1 1/4	1.5	7,270	6,540										

Ⓢ表示数量超えはWOSIにてご確認ください。

■ くい込み継手タイプ

Type	材質
SNSUS	SUS304

RoHS10

型式		D	A	B	C	d	L	L1	F	対辺		¥基準単価
Type	No.									本体h	ナットH	1~4コ
SNSUS	1S	4	50.5	43.5	6	4	43.8	19	15.3	14	14	8,000
		6.35			8	6	43.9	19	15.4	14	14	8,200
	1.5S	6			9.53	7	48.9	24	15.4	14	14	8,500
		6.35			12.7	10	52.9	28	15.4	14	14	9,000
	2S	6.35			10	8	49.8	24	16.8	14	15.87	9,000
		8			12.7	10	49.8	24	16.8	14	15.87	9,000

ⓈDは適用管外径です。適用管P1353

Ⓢ表示数量超えはWOSIにてご確認ください。

■ フランジ×フェールルタイプ

Type	材質
SNZFR	SUS304

*フランジ: 10K

RoHS10

型式		呼び	D	D1	d	d1	A	L	(T)	P.C.D.	¥基準単価	¥スライド単価					
Type	No.										1~4コ	5~10					
SNZFR	1S	20A	25.4	100	23	15	50.5	54	14	75	12,090	10,460					
		25A								90	12,620	10,830					
		32A								100	12,830	10,900					
	1.5S	40A								105	13,310	10,900					
		40A								140	105	13,360	11,300				
		50A								155	120	13,890	11,950				
	2S	50A								155	120	17,180	14,600				
		65A								175	140	18,450	15,700				
	2.5S	50A								155	59.5	77.5	58	18	140	18,450	15,700

Ⓢ内面のミビード除去及び研磨を行います。

Ⓢ表示数量超えはWOSIにてご確認ください。

■ フランジ×ネジシートタイプ

Type	材質
SNZFY	SUS304

*フランジ: 10K

RoHS10

型式		呼び	D	d	d1	L	(T)	P.C.D.	¥基準単価	
Type	No.								1~4コ	
SNZFY	1S	20A	100	23	15	54	14	75	12,400	
		25A						90	12,900	
		32A						100	13,100	
	1.5S	40A						105	13,100	
		40A						140	105	13,600
		50A						155	120	14,100
	2S	50A						155	120	17,200
		65A						175	140	18,400

Ⓢ内面のミビード除去及び研磨を行います。

Ⓢ表示数量超えはWOSIにてご確認ください。

Ⓢねじ部はID規格のねじとなります。

Order 注文例
型式 呼び
SNZFA1S 4

Delivery 出荷日
●右記以外 翌日出荷
●SNZFY 8 日日出荷
●在庫品 即日P133
Ⓢご希望によりPM6:00迄、
当日出荷受付致します。