


●鋼からステンレス鋼そしてアルミ材まで、高速・高能率加工ができるオイルホールドリルです。

This oil hole drill is adapted in workpiece material from Carbon Steel and Stainless Steel to Aluminum.



新商品

LIST 7580P

オーダー方法 **SGOH** 直径

直径8.0~9.9
在庫品限り

単位 (Unit) : mm

| 直径 Dc | 溝長 ℓ | 全長 L | シャンク径 Ds | シャンク長 ℓs | 在庫 Stock | 参考価格(円) Price (¥) | |
|-------|------|------|----------|----------|----------|-------------------|---|
| 8.0 | 56 | 124 | 16 | 48 | | - | |
| 8.1 | 60 | 128 | | | | | |
| 8.2 | | | | | | | |
| 8.3 | | | | | | | |
| 8.4 | | | | | | | |
| 8.5 | | | | | | | |
| 8.6 | | | | | | | |
| 8.7 | | | | | | | |
| 8.8 | | | | | | | |
| 8.9 | | | | | | | |
| 9.0 | | | | | | □ | |
| 9.1 | 65 | 133 | | | | | |
| 9.2 | | | | | | | |
| 9.3 | | | | | | | |
| 9.4 | | | | | | | |
| 9.5 | | | | | | | |
| 9.6 | | | | | | | |
| 9.7 | | | | | | | |
| 9.8 | 70 | 138 | | | | | |
| 9.9 | | | | | | | |
| 10.0 | | | | | ● | 25,200 | |
| 10.1 | 75 | 144 | | | | | |
| 10.2 | | | | | | | |
| 10.3 | | | | | | | |
| 10.4 | | | | | | | |
| 10.5 | | | | | ● | 25,200 | |
| 10.6 | | | | | | | |
| 10.7 | | | | | | | |
| 10.8 | | | | | | | |
| 10.9 | | | | | | | |
| 11.0 | | | 80 | 149 | | | ● |
| 11.1 | | | | | | | |
| 11.2 | | | | | | | |
| 11.3 | | | | | | | |
| 11.4 | | | | | | | |
| 11.5 | | | | | ● | 25,700 | |
| 11.6 | | | | | | | |
| 11.7 | | | | | | | |
| 11.8 | 86 | 155 | | | | | |
| 11.9 | | | | | ● | 25,800 | |
| 12.0 | | | | | | | |
| 12.1 | | | | | | | |
| 12.2 | | | | | | | |
| 12.3 | | | | | | | |
| 12.4 | | | | | | | |
| 12.5 | | | | | ● | 25,800 | |
| 12.6 | | | | | | | |
| 12.7 | | | | | | | |
| 12.8 | 92 | 161 | | | ● | 30,100 | |
| 12.9 | | | | | | | |
| 13.0 | | | | | | | |
| 13.1 | | | | | | | |
| 13.2 | | | | | | | |
| 13.3 | | | | | ● | 30,100 | |
| 13.4 | | | | | | | |
| 13.5 | | | | | | | |
| 13.6 | | | | | | | |
| 13.7 | | | | | | | |
| 13.8 | | | | | | | |
| 13.9 | | | | | | | |

| 直径 Dc | 溝長 ℓ | 全長 L | シャンク径 Ds | シャンク長 ℓs | 在庫 Stock | 参考価格(円) Price (¥) | | |
|-------|------|------|----------|----------|----------|-------------------|---|--------|
| 14.0 | 97 | 166 | 16 | 48 | ● | 30,400 | | |
| 14.1 | | | | | | | | |
| 14.2 | | | | | | | | |
| 14.3 | | | | | | | □ | |
| 14.4 | | | | | | | | |
| 14.5 | | | | | | | ● | 30,400 |
| 14.6 | | | | | | | | |
| 14.7 | | | | | | | | |
| 14.8 | | | | | | | | |
| 14.9 | | | □ | | | | | |
| 15.0 | 102 | 177 | 20 | 50 | ● | 34,300 | | |
| 15.1 | | | | | | | | |
| 15.2 | | | | | | | | |
| 15.3 | | | | | | | □ | |
| 15.4 | | | | | | | | |
| 15.5 | | | | | | | ● | 34,300 |
| 15.6 | | | | | | | | |
| 15.7 | | | | | | | | |
| 15.8 | | | | | | | | |
| 15.9 | | | | | | | □ | |
| 16.0 | 107 | 182 | 20 | 50 | ● | 36,900 | | |
| 16.1 | | | | | | | | |
| 16.2 | | | | | | | | |
| 16.3 | | | | | | | □ | |
| 16.4 | | | | | | | | |
| 16.5 | | | | | | | ● | 36,900 |
| 16.6 | | | | | | | | |
| 16.7 | | | | | | | | |
| 16.8 | | | | | | | | |
| 16.9 | | | | | | | □ | |
| 17.0 | 113 | 188 | 25 | 56 | ● | 39,600 | | |
| 17.1 | | | | | | | | |
| 17.2 | | | | | | | | |
| 17.3 | | | | | | | □ | |
| 17.4 | | | | | | | | |
| 17.5 | | | | | | | ● | 39,600 |
| 17.6 | | | | | | | | |
| 17.7 | | | | | | | | |
| 17.8 | | | | | | | | |
| 17.9 | | | □ | | | | | |
| 18.0 | 118 | 193 | 25 | 56 | ● | 42,500 | | |
| 18.1 | | | | | | | | |
| 18.2 | | | | | | | | |
| 18.3 | | | | | | | □ | |
| 18.4 | | | | | | | | |
| 18.5 | | | | | | | ● | 42,500 |
| 18.6 | | | | | | | | |
| 18.7 | | | | | | | | |
| 18.8 | | | | | | | | |
| 18.9 | | | | | | | □ | |
| 19.0 | 123 | 206 | 25 | 56 | ● | 45,500 | | |
| 19.1 | | | | | | | | |
| 19.2 | | | | | | | | |
| 19.3 | | | | | | | □ | |
| 19.4 | | | | | | | | |
| 19.5 | | | | | | | ● | 45,500 |
| 19.6 | | | | | | | | |
| 19.7 | | | | | | | | |
| 19.8 | | | | | | | | |
| 19.9 | | | | | | | □ | |

超硬ドリル

ハイスドリル

タップ

超硬
エンドミル

ハイス
エンドミル

切断工具

バック・
セット商品
その他

精密工具

技術資料
索引