
G テーパシャンク ショート ドリル G Taper Shank Short Drills

●鋼からステンレス鋼そしてアルミまで、高能率加 工ができます。高い位置精度が得られます。

This drill having short length is suitable for high-speed drilling of most material from Stainless Steel to Aluminum.





新商品

LIST 6618P

オーダ方法 GTS 直径									
直径 Dc	溝長 ℓ	全長 L	シャンク MT No.	在庫 Stock	参考価格(円) Price (¥)				
7.0	45	126		•	7,440				
7.1 7.2					_				
7.3					-				
7.4 7.5					7,810				
7.6	49	130			_				
7.7 7.8					-				
7.9					_				
8.0 8.1					7,830				
8.2					_				
8.3					-				
8.4 8.5					8,000				
8.6	52	133			-				
8.7 8.8					_				
8.9					-				
9.0 9.1				•	8,200				
9.2					_				
9.3 9.4					-				
9.5					8,410				
9.6					_				
9.7 9.8					-				
9.9	56	137	1		-				
10.0					8,910				
10.2					_				
10.3 10.4					-				
10.5					9,220				
10.6 10.7	61	142			-				
10.7					_				
10.9					-				
11.0 11.1					9,980				
11.2					_				
11.3 11.4					_				
11.5				•	10,500				
11.6 11.7					-				
11.8					_				
11.9 12.0	66	147			10,700				
12.1					-				
12.2 12.3					-				
12.4					_				
12.5 12.6				•	11,300				
12.7					_				
12.8					-				
12.9 13.0				•	11,300				
13.1				_	-				
13.2					-				

直径 Dc	溝長 ℓ	全長 L	シャンク MT No.	在庫 Stock	参考価格(円) Price (¥)
13.4		151	1		-
13.5				•	12,400
13.6 13.7	70				_
13.8	70				_
13.9					-
14.0 14.1				•	13,100
14.2		171			-
14.3	73				_
14.4					-
14.5 14.6				•	13,500
14.7					-
14.8					_
14.9 15.0					14,100
15.1					-
15.2		175			_
15.3 15.4					-
15.4					14,700
15.6	77				_
15.7					_
15.8 15.9					_
16.0					15,300
16.1		179			_
16.2	81				_
16.3 16.4			2		_
16.5					16,100
16.6					_
16.7 16.8					_
16.9					-
17.0					17,000
17.1 17.2	84	182			_
17.3					_
17.4					-
17.5				•	17,800
17.6 17.7					-
17.8					-
17.9					
18.0 18.1				•	18,700
18.2	87	185			_
18.3					-
18.4 18.5					19,400
18.6					19,400
18.7					-
18.8 18.9					_
19.0				•	20,200
19.1	90	188			-
19.2					-
19.3 19.4					-
19.5				•	21,400
19.6					_

超硬ドリル

単位 (Unit):mm

ハイスドリル

タップ

超硬 エンドミル

ハイス エンドミル

切断工具

パック・ セット商品 その他

精密工具

技術資料 索引