





隔壁用ユニオン:KGE



適用チューブ 外径mm	型式	T(M)	H (六角 対辺)	L	取付穴	M	注)有効断面積 mm <sup>2</sup>		質量 g
							ナイロン	ウレタン	
4	KGE04-00	M12×1	14	32.5	13	16	5.6	4	26
6	KGE06-00	M14×1	17	34.5	15	17	13.1	10.4	33
8	KGE08-00	M16×1	19	38	17	18.5	26.1	18.0	52
10	KGE10-00	M20×1	24	42.5	21	21	41.5	29.5	70
12	KGE12-00	M22×1	27	44	23	22	58.3	46.1	90
16	KGE16-00	M28×1.5	32	51	29	25	113	(96)	115

注) ( )内寸法はソフトナイロンの場合


隔壁用メスユニオン:KGE



適用チューブ 外径mm	接続ねじ Rcねじ	型式	T(M)	H1 (六角 対辺)	H2 (六角 対辺)	L1	L2	取付穴	M	注)有効断面積 mm <sup>2</sup>		質量 g									
										ナイロン	ウレタン										
4	1/8	KGE04-01	M12×1	14	14	27.5	11	13	16	5.6	4	16									
	1/4	KGE04-02		17		31	15					35									
6	1/8	KGE06-01	M14×1	17	17	31.5	15	15	17	13.1	10.4	30									
	3/8	KGE06-03										19	33.5	17	29						
	1/8	KGE08-01										M16×1	17	19	27.5	7.5	17	18.5	26.1	18.0	28
1/4	KGE08-02	33	13	27																	
8	3/8	KGE08-03	M16×1	19	19	35	15	17	18.5	26.1	18.0	48									
	1/4	KGE10-02										M20×1	22	24	34.5	12.5	21	21	41.5	29.5	53
	3/8	KGE10-03													36.5	14					67
10	3/8	KGE12-03	M20×1	22	24	37	14	23	22	58.3	46.1	92									
	1/2	KGE12-04										41	18	59							
	3/8	KGE16-03										M28×1.5	30	32	40	14	29	25	96	(96)	127
1/2	KGE16-04	44	18	113	132																

注) ( )内寸法はソフトナイロンの場合

チューブキャップ:KGC



適用チューブ 外径mm	型式	øD	L	M	質量 g
4	KGC04-00	10.4	17	16	3
6	KGC06-00	12.8	18.5	17	3
8	KGC08-00	15.2	20.5	18.5	4
10	KGC10-00	18.5	23	21	6
12	KGC12-00	20.9	24	22	8
16	KGC16-00	26.5	28	25	13

KQ2

KQB2

KS  
KX

KM

KF

M

H/DL  
L/LL

KC

KK

KK130

DM

KDM

KB

KR

KA

KQG2

KQ2-G

KG

KFG2

MS

KF□  
KQ□

KQ  
X1744

KKA

KP

LQ

MQR

T

IDK