

異径継手

—黄銅タイプ—



Order
注文例

Type

H02

No.


C102

■異径シリーズオス継手



ロット販売

CAD 3D




材質 黄銅

■異径シリーズオスエルボ



ロット販売

CAD 3D



材質 黄銅

型式		T ₁ (R)	適用管径 D	T ₂ (UNF)	L	対辺		E	箱入数
Type	No.					H			
H02	C102	1/8	1/4	7/16-20	26	12	4.8	50	
	C1025		5/16	1/2-20	27	13	5.5		
	C103-1		3/8	5/8-18	29	17	4.8		
	C202	1/4	1/4	7/16-20	26	12	4.8		
	C2025		5/16	1/2-20	30	14	5.5		
	C203		3/8	9/16-18	31	15	7.2		
	C203-1	1/2	3/8	5/8-18	32	17	8.0		
	C204			1/2	3/4-16	36	21		4.8
	C205			5/8	7/8-14	37	23		5.5
	C302	3/8	1/4	7/16-20	29	17	7.2		
	C3025		5/16	1/2-20	30	17	8.0		
	C303		3/8	9/16-18	31	17	9.0		
	C303-1	1/2	3/8	5/8-18	32	21	10.3		
	C304			1/2	3/4-16	36	21		10.5
	C305			5/8	7/8-14	37	23		4.8
	C402	1/2	3/8	1/4	7/16-20	33	21		5.5
	C4025			5/16	1/2-20	34	21		7.2
	C403			9/16-18	35	21	10.3		
	C403-1	3/4	3/8	5/8-18	35.5	23	12.7		
	C404			1/2	3/4-16	38.5	23		7.2
	C405			5/8	7/8-14	39.5	23		10.3
	C603-1	3/4	3/8	5/8	7/8-14	41	27		12.7
	C604			1/2	3/4-16	40	27		12.7
	C605			5/8	7/8-14	41	27		15.9
C606	3/4	1 1/16-14	43	27	15.9				

型式		T ₁ (R)	適用管径 D	T ₂ (UNF)	L ₁	L ₂	対辺		E	箱入数
Type	No.						H			
H03	L1015	1/8	3/16	3/8-24	18	21	9.5	3.2		
	L102		1/4	7/16-20	21.5	4.8				
	L1025		5/16	1/2-20	20	23.5	11			
	L103	1/4	3/8	7/16-20	20.5	25.5	13	5.5		
	L103-1			1/2-20	26.5					
	L104			1/2	9/16-18	23	30	4.8		
	L202	1/2	3/8	1/4	5/8-18	23.5	23	11		
	L2025			5/16	3/4-16	24	24.5	5.5		
	L203			9/16-18	25.5	24	7.2			
	L203-1	3/8	5/8	5/8-18	24	26.5	13	8.0		
	L204			1/2	3/4-16	25.5	30			
	L205			5/8	7/8-14	27	32	17		
	L302	3/8	3/8	1/4	7/16-20	24	23	11	4.8	
	L3025			5/16	1/2-20	25	24.5	5.5		
	L303			9/16-18	25.5	25.5	7.2			
	L303-1	1/2	3/8	5/8-18	26	27	13	9.0		
	L304			1/2	3/4-16	25.5	30	10.5		
	L305			5/8	7/8-14	27	32	17		
	L402	1/2	3/8	1/4	7/16-20	31.5	28.5	15	4.8	
	L4025			5/16	1/2-20	29	29	5.5		
	L403			9/16-18	31	30	7.2			
	L403-1	3/4	3/8	5/8-18	31.5	31	17	10.3		
	L404			1/2	3/4-16	32	32	12.7		
	L405			5/8	7/8-14	32	32	12.7		
L604	3/4	3/8	1/2	3/4-16	34	35	21	10.3		
L605			5/8	7/8-14	34	35	21	12.7		
L606			3/4	1 1/16-14	36	36	15.9			

使用温度範囲		-53℃～+121℃	
最高 使用 圧力	室温20℃において、赤銅管を使用		
	赤銅管径(インチ)	最高使用圧力Mpa	
	1/8	17.5	
	1/4	10	
	3/8	7	
	1/2	5	
	5/8	4	
3/4	3.5		
7/8	3		

Ⓢ 上記数値は参考値で、保証値ではありません。