

スプロケット ロックスプロケット Sタイプ

RS40

すべて歯先硬化処理品です。

形番	ピッチ円直径 D_p	(外径) (D_o)	ハブ径 D_H	ハブ長さ L	適用軸穴径 ϕd										歯数			
					24	25	28	30	32	35	38	40	42	45				
※RS40-1B15TQ-S33□□A	61.08	67	46	22	●	●	●											15
RS40-1B16TQ-S33□□■	65.10	71	50	22	●	●	●											16
RS40-1B17TQ-S44□□■	69.12	76	54	22	●	●	●	●	●	●								17
RS40-1B18TQ-S44□□■	73.14	80	57	22	●	●	●	●	●	●								18
RS40-1B19TQ-S44□□■	77.16	84	62	22	●	●	●	●	●	●								19
RS40-1B20TQ-S48□□■	81.18	88	67	25	●	●	●	●	●	●								20
RS40-1B20TQ-S56□□■														●	●	●	●	
RS40-1B21TQ-S48□□■	85.21	92	71	25	●	●	●	●	●	●								21
RS40-1B21TQ-S56□□■														●	●	●	●	
RS40-1B22TQ-S48□□■	89.24	96	75	25	●	●	●	●	●	●								22
RS40-1B22TQ-S56□□■														●	●	●	●	
RS40-1B23TQ-S48□□■	93.27	100	77	25	●	●	●	●	●	●								23
RS40-1B23TQ-S56□□■														●	●	●	●	
RS40-1B24TQ-S48□□■	97.30	104	63	25	●	●	●	●	●	●								24
RS40-1B24TQ-S56□□■														●	●	●	●	
RS40-1B25TQ-S48□□■	101.33	108	63	25	●	●	●	●	●	●								25
RS40-1B25TQ-S56□□■														●	●	●	●	
RS40-1B26TQ-S48□□■	105.36	112	63	25	●	●	●	●	●	●								26
RS40-1B26TQ-S56□□■														●	●	●	●	
RS40-1B27TQ-S48□□■	109.40	116	63	25	●	●	●	●	●	●								27
RS40-1B27TQ-S56□□■														●	●	●	●	
RS40-1B28TQ-S48□□■	113.43	120	63	25	●	●	●	●	●	●								28
RS40-1B28TQ-S56□□■														●	●	●	●	
RS40-1B30TQ-S48□□■	121.50	128	63	25	●	●	●	●	●	●								30
RS40-1B30TQ-S56□□■														●	●	●	●	
RS40-1B32TQ-S48□□■	129.57	137	68	28	●	●	●	●	●	●								32
RS40-1B32TQ-S56□□■														●	●	●	●	
RS40-1B34TQ-S48□□■	137.64	145	68	28	●	●	●	●	●	●								34
RS40-1B34TQ-S56□□■														●	●	●	●	
RS40-1B35TQ-S48□□■	141.68	149	68	28	●	●	●	●	●	●								35
RS40-1B35TQ-S56□□■														●	●	●	●	
RS40-1B36TQ-S48□□■	145.72	153	68	28	●	●	●	●	●	●								36
RS40-1B36TQ-S56□□■														●	●	●	●	
RS40-1B38TQ-S48□□■	153.79	161	68	28	●	●	●	●	●	●								38
RS40-1B38TQ-S56□□■														●	●	●	●	
RS40-1B40TQ-S48□□■	161.87	169	68	28	●	●	●	●	●	●								40
RS40-1B40TQ-S56□□■														●	●	●	●	

形番末尾の□□には軸穴寸法をご記入、■には、取付形式AまたはBをご記入ください。●印が対応軸穴径です。
注) ※の形番は取付形式Aのみ対応可能です。取付形式Bはできません。

■ RS40 ロックスプロケット(Sタイプ) 最大許容伝達トルク一覧表

(単位 N・m)

軸穴径 歯数	14	15	16	17	18	19	20	22	24	25	28	30	32	35	38	40	42	45
14T																		
15T	121																	
16T		139	149	158	167	177	186	205										
17T																		
18T									223	232	260	279	298	325				
19T																		
20T																		
21T																		
22T		174	186															
23T																		
24T				198	209	221	232	256										
25T									446	465	521	558	595	651	530	558	586	628
26T																		
27T																		
28T																		
30T																		
32T																		
34-40T																		

ご使用になる前に

汎用

無給油

強力

耐環境

特殊

スプロケット

ポンギヤドライブ

アクセサリ

技術ノート