


インサート ネガティブタイプ

- : 連続加工
- : 軽断続加工
- ✳: 強断続加工

TN



材料	コーティング	連続加工	軽断続加工	強断続加工
P 鋼		●	○	✳
M ステンレス		○	○	
K 鋳鉄		○	○	
N 非鉄金属				
S 難削材				
H 高硬度材				



用途	プレーカ 記号	形番	コーティング													コーテッド サーメット	サーメット	超硬	寸法 (mm)																
			T9205	T9215	T9225	T9235	T9115	T9125	T9135	T6120	T6130	AH630	AH645	AH8005	AH8015				T515	T5105	T5115	T5125	AH120	AH725	GH330	GT720	NS9530	TH10	RE	IC	S	D1			
中切削		TNMG160404-28																									●	0.4	9.525	4.76	3.81				
		TNMG160408-28																										●	0.8	9.525	4.76	3.81			
		TNMG220404-28																											●	0.4	12.7	4.76	5.16		
		TNMG220408-28																											●	0.8	12.7	4.76	5.16		
		TNMG160404-33																										●	0.4	9.525	4.76	3.81			
		TNMG160408-33																											●	0.8	9.525	4.76	3.81		
		TNMG160416-33			●			▲																						1.6	9.525	4.76	3.81		
		TNMG220404-33			●			▲															●							0.4	12.7	4.76	5.16		
		TNMG160404-37		●				▲																					●	0.4	9.525	4.76	3.81		
		TNMG160408-37		●				▲																						●	0.8	9.525	4.76	3.81	
			TNMG160404-38																											●	0.4	9.525	4.76	3.81	
			TNMG160408-38																												●	0.8	9.525	4.76	3.81
V		TNMG110404E-SM								●	●	●																							
		TNMG110408E-SM								●	●	●																							
		TNMG160404-SM								●	●	●	●									●													
		TNMG160408-SM								●	●	●	●									●													
		TNMG160412-SM								●	●	●	●																						
		TNMG220408-SM								●	●	●	●																						
W		TNMG220412-SM							●	●	●	●																							
		TNMG160404-CM																																	
		TNMG160408-CM																																	
		TNMG160412-CM																																	
Y		TNMG220408-CM																																	
		TNMG220412-CM																																	
		TNMG160404-CM																																	
		TNMG160408-CM																																	

- : 設定アイテム
- ▲: 将来廃止予定アイテム

参照ページ: 外径ホルダ → C025 - 内径ホルダ → D044 - J series ホルダ → G045 -
カートリッジ → K193 -