

管継手

—ミリタイプ—

選定手順①～③より型式・数値を選択の上、ご注文ください。



Order
注文例



型式 (①Type・②No.・③管ねじ)

MC04M03T

型式 (Type・No.)


U06M

■おねじコネクタ継手 (ミリタイプ用)



材質 SUS316

■エルボ (ミリタイプ用)




材質 SUS316

| 型式 | | | D | T | L | E | 対辺 | |
|-------|------|------|------|------|------|-----|-----|------|
| ①Type | ②No. | ③管ねじ | | | | | 本体h | ナットH |
| MC | 04M | 03T | φ 4 | 1/8 | 32 | 2.4 | 12 | 12 |
| | | 06T | | 1/4 | 37 | | | |
| | 06M | 03T | φ 6 | 1/8 | 34.5 | 4.8 | 14 | 14 |
| | | 06T | | 1/4 | 38.3 | | | |
| | | 10T | | 3/8 | 39.3 | | | |
| | 08M | 03T | φ 8 | 1/8 | 34.3 | 5 | 14 | 16 |
| | | 06T | | 1/4 | 38.3 | | | |
| | | 10T | | 3/8 | 39.3 | 6.4 | 17 | |
| | | 15T | | 1/2 | 44.3 | | | |
| | 10M | 06T | φ 10 | 1/4 | 39.3 | 8 | 17 | 19 |
| | | 10T | | 3/8 | 40.3 | | | |
| | | 15T | | 1/2 | 45.3 | | | |
| 12M | 06T | φ 12 | 1/4 | 42.3 | 9.5 | 21 | 22 | |
| | 10T | | 3/8 | 43.3 | | | | |
| | 15T | | 1/2 | 48.3 | | | | |


| 型式 | | | D | T | L | L1 | E | E1 | 対辺 | | |
|-------|------|------|------|-----|------|------|-----|-----|-----|------|------|
| ①Type | ②No. | ③管ねじ | | | | | | | 本体h | ナットH | |
| ME | 06M | 03T | φ 6 | 1/8 | 32 | 25 | 4.8 | 5 | 7 | 14 | |
| | | 06T | | 1/4 | 32.5 | 22.7 | | | | | |
| | 08M | 03T | φ 8 | 1/8 | 31.8 | 23.2 | 6.4 | 5 | 5 | 7 | 16 |
| | | 06T | | 1/4 | 32.6 | 23 | | | | | |
| | | 10T | | 3/8 | 34 | 27 | | | | | |
| | 10M | 03T | φ 10 | 1/8 | 38.4 | 28.4 | 7 | 5 | 5 | 7 | 18.9 |
| | | 06T | | 1/4 | 34.2 | 26.1 | | | | | |
| | | 10T | | 3/8 | 34 | 27 | 9.6 | 7.6 | 9.6 | | |
| | | 15T | | 1/2 | 39.1 | 31.2 | | | | | |
| | 12M | 10T | φ 12 | 3/8 | 41.3 | 29.9 | 9.5 | 9.6 | 12 | 7 | 22.7 |
| | | 15T | | 1/2 | 41.5 | 32 | | | | | |

■ユニオン継手 (ミリタイプ用)



材質 SUS316

■ユニオンエルボ (ミリタイプ用)




材質 SUS316

| 型式 | | D | L | E | 対辺 | |
|------|-----|------|------|-----|-----|------|
| Type | No. | | | | 本体h | ナットH |
| U | 06M | φ 6 | 42.6 | 4.8 | 14 | 14 |
| | 08M | φ 8 | | | | |
| | 10M | φ 10 | 44.6 | 8 | 17 | 19 |
| | 12M | φ 12 | | | | |

| 型式 | | D | L | E | 対辺 | |
|------|-----|------|------|-----|------|------|
| Type | No. | | | | 本体h | ナットH |
| UE | 06M | φ 6 | 32.5 | 4.8 | 14.5 | 14 |
| | 08M | φ 8 | | | | |
| | 10M | φ 10 | 34.7 | 8 | 18.6 | 19 |
| | 12M | φ 12 | | | | |

■フェルール(ミリタイプ用)



材質 SUS316

| 型式 | | D |
|------|-----|------|
| Type | No. | |
| F | 03M | φ 3 |
| | 04M | φ 4 |
| | 06M | φ 6 |
| | 08M | φ 8 |
| | 10M | φ 10 |
| | 12M | φ 12 |