

選定手順①～③より型式・数値を選択の上、ご注文ください。



Order
注文例

型式(①Type・②D) - ③呼び

EPC3
EPLH6
EGPLL4
EGPL4


M3C
M5
01
M5

■メイルコネクタ



ロット販売

CAD 2D 3D



材質 黄銅


型式		③呼び	K	A	L	P	C	二面幅 H	E	X	Y	箱入数
①Type	②D											
EPC	3	M3C	M3×0.5	3.0	15.0	5.5	8.3	5.5	3.0	7.0	6.0	200
		M5C	M5×0.8	3.5	15.6			8.0				
	4	M3C	M3×0.5	3.0	17.0	8.0	9.6	5.5	3.8	9.7	7.7	
		M5C	M5×0.8	3.5	17.6			8.0				
	6	M5C	M5×0.8	3.5	17.6	10.0	10.2	8.0	4.0	11.8	9.8	
		01C	R1/8	8.0	20.8			10.0				

■45°エルボ



ロット販売

CAD 2D 3D




材質 黄銅/PBT

型式		③呼び	ねじ サイズR	L	A	B	C	E	ϕD	二面幅 H	X	Y	箱入数	
①Type	②D													
EPLH	6	M5	M5	36.1	21.9	4	17	15.5	6	12	13.9	12.5	100	
		01	R1/8	42	24.4			7.5						
	8	02	R1/4	48	27.6			20.6	18.3	8	14	15.9	13.9	50
		10	02	R1/4	55.6	32.2		9.5	23.1	20.5	10	17	19.5	17
	12	03	R3/8	61.9	37.2			26	22.9	12	21	23	20.5	25
		03	R3/8	62.9	35.5	10.5								

■ロングエルボ



ロット販売




材質 黄銅/PBT

型式		③呼び	ねじ サイズR	A	B	C	ϕD	E	二面幅 H	X	Y	箱入数	
①Type	②D												
EGPLL	4	01		7.5	32.4	14.9	4	18.8	10	11.9	10.5	50	
		01	R1/8	9.5	33.5	16	6	20	14	13.9	12.5		
	6	02	R1/4	9.5	35				14				25
		01	R1/8	7.5	35.8				10				
	8	02	R1/4	9.5	37.3	18.3	8	22.5	14	15.9	13.9		25
		03	R3/8	10.5	38.8				17	19.5	17		
	10	02	R1/4	9.5	48.3	21	10	26.9	17	19.5	17	10	
		03	R3/8	10.5	49.3	22.6	12	28.5	23	20.5	10		

■メイルエルボ



ロット販売



材質 黄銅/PBT

型式		③呼び	ねじ サイズR	A	B	C	ϕD	E	二面幅 H	X	Y	箱入数	
①Type	②D												
EGPL	4	M5	M5	4	18.5				8			100	
		01	R1/8	7.5	18.4	14.9	4	18.8	10	11.9	10.5		
	6	02	R1/4	9.5	19.9				14				50
		M5	M5	4	19.6				8				
	8	01	R1/8	7.5	19.5				10	13.9	12.5		50
		02	R1/4	9.5	21	16	6	20	14				
	10	03	R3/8	10.5	22.5				17			25	
		01	R1/8	7.5	22.9				10				
	12	02	R1/4	9.5	21.5	18.3	8	22.5	14	15.9	13.9	25	
		03	R3/8	10.5	23				17				
	16	01	R1/8	7.5	24.3				21	19.5	17	20	
		02	R1/4	9.5	26.3	21	10	26.9	21				
	16	03	R3/8	10.5	24.8				21			20	
		04	R1/2	13.5	27.8				21				
	16	03	R3/8	10.5	26.3	22.6	12	28.5	17	23	20.5	20	
		04	R1/2	13.5	29.3				21				
16	03	R3/8	10.5	33.7				20	27	24	20		
	04	R1/2	13.5	36.7	25	16	33.5	21					

ロット
販売

①お問合わせやご注文の際に、
単品数量の倍数でお問合わせ、
ご注文ください。
例: EPH4-01→50コ、100コ

仕様(参考値)

使用流体	空気、真空
使用圧力範囲	0~1.0MPa
負圧	-100KPa
耐圧	1.5MPa
使用温度範囲	0~60℃
適用チューブ	ナイロンおよびポリウレタンチューブ