

ワンタッチ継手 / 圧力計コネクタ / チェックバルブ

選定手順①～③より型式・数値を選択の上、ご注文ください。



Order
注文例

型式 (Type・No.)

CNHM4-01

型式 (①Type・②No.)

SQRC4-M5


③制御方式

A


■メイルコネクタ



Type	材質	S表面処理
CNHM	黄銅	ニッケルメッキ



■メイルコネクタ



材質 黄銅


型式		チューブ径	ねじ径	A	B	C	G	L	二面幅	有効断面積	質量
Type	No.	D	R						H	(mm ²)	(g)
CNHM	4-M5	4	M5	3.6	15.6			19.3	10	4	5
	4-01		R1/8	6	16.5	14.2	10	19.5	10	5.5	6
	4-02		R1/4	9	14.3			18.8	14		13
	6-M5	6	M5	3.6	18.3	16.9	12	22	12	4	8
	6-01		R1/8	6	18.6			21.6	12	12.5	15
	6-02		R1/4	9	19.2	17.1	12.4	23.7	14		23
	6-03	R3/8	9	17			21.5	17		19	
	8-01	8	R1/8	6	23.7			26.7	14	20	12.5
	8-02		R1/4	9	23	18.7	14	26	14		15
	8-03		R3/8	9	17.1			21.6	14		19
	10-01	10	R1/8	6	25.7			28.7	17	22	21
	10-02		R1/4	9	27.2	20.7	17	31.7	17		23
	10-03		R3/8	9	23.2			27.5	17		25
	10-04	12	R1/2	11	22.2			37.5	21	35	40
	12-02		R1/4	9	30			34.5	21		36
	12-03		R3/8	9	25.7	22.8	20.4	30.8	21		27
12-04	R1/2	11	25.2							29	

型式		チューブ径	ねじ径	A	B	L	二面幅	有効断面積	質量
Type	No.	D	R				H	(mm ²)	(g)
MSQC	4-M3	phi4	M3x0.5	3.5	15.2	16.9	8	1.33	2.8
	4-M5		M5x0.5	4	15.1			4.91	3.3
	4-01		R1/8	6	11.4	14.5		6.16	5.2
	6-M5	phi6	M5x0.5	4	16	18.1	10	4.91	4.3
	6-01		R1/8	6	13.9	17.1		15.9	7

■圧力計コネクタ



SQCG15-01




材質 PBT

■チェックバルブ



Type	材質
SQRC	黄銅



■仕様 (参考値)

使用流体	空気、真空
使用圧力範囲 kgf/cm ² (kPa)	0~9(0~900)
保証耐圧力 kgf/cm ² (kPa)	10(1000)
保証真空圧力 kPa (Torr)	-100(10)
使用温度範囲 °C	5~60

型式		チューブ径	ねじ径	A	B	C	G	L	二面幅	有効断面積	質量	
①Type	②No.	③流れ方向	D						H	(mm ²)	(g)	
SQRC	4-M5	A	phi4	M5	3.6	30		31.7	10	3.9	11.5	
	4-01			R1/8	6	24.5	13.9	10	27.5	10	4.9	10.5
	6-01			R1/8	6	28.8			31.8	12	15.5	
	6-02		R1/4	9	27.3	15.6	12.4			12.5	22	
	8-01		R1/8	6	30.5	16.8	14	33.5	14	19.6	21	
	8-02		R1/4	9	29							
	10-03	B	phi6	R3/8	12	56.4	25	62.4	24	45		
	10-04			R1/2	15	60.5	28	68.5	27	50.5		
	12-03			R3/8	12	58.4	25	64.4	24	42		
	12-04		R1/2	15	63	22.3	25	64.4	24	47.5		