



SN□□ (ネガティブ)

型式	寸法					ブレード	用途	P 鋼		M ステンレス			K 鋳物	
	L	LC	S	d	r			YBC152	YBC252	YBM251	YBG203	YBG205	YBD152	YBD252
SNMG 120404	12.7	12.7	4.76	5.16	0.4	DF	仕上							
						DM	中	●	●					
						EM	中			●				
						PM	断続							
SNMG 120408	12.7	12.7	4.76	5.16	0.8	DF	仕上	●	●					
						DM	中	●	●				●	
						EM	中				●			
						PM	断続		●				●	●
						全周	中～粗							
SNMG 120412	12.7	12.7	4.76	5.16	1.2	DF	仕上		●					
						DM	中		●				●	
						EM	中				●	●		
						PM	断続							●
						全周	中～粗							
SNMG 190616	19.05	19.05	6.35	7.94	1.6	DR	粗							
						HDR	粗～重							
SNMG 190624	19.05	19.05	6.35	7.94	2.4	HDR	粗～重							
SNMG 250724	25.4	25.4	7.94	9.12	2.4	ER	粗							
						DR	粗							
SNMG 250924	25.4	25.4	9.525	9.12	2.4	HDR	粗～重							

**PSBNR/L**  
Kr:75°

型式	在庫		基本寸法(mm)						ボルト	シム	レンチ	レバーピン	止めピン	
	R	L	a	b	L	h	s	e						
PSBNR/L			16	16	100	16	13	21	LEM6x13.4A	S09AP	WH25L	L3	SP10	
	1616H09													
	2020K09			20	20	125	20	17						23
	2020K12			20	20	125	20	17	28	LEM8x21	S12AP	WH30L	L4	SP4
	2525M12			25	25	125	25	22	28					
	3225P12			32	25	170	32	22	28					
	3232P12			32	32	170	32	27	28	LEM8x25	S15AP	WH30L	L5	SP5
	2525M15			25	25	150	25	22	35					
	3232P15			32	32	170	32	27	35					
	3232P19			32	32	170	32	27	40	LEM10x27	S19AP	WH40L	L6	SP6
	4040S19			40	40	250	40	35	40					
	4040S2507			40	40	250	40	35	48					
4040S2509			40	40	250	40	35	48	S25AP-09	S25AP	WH50L	L8	SP8	